



## ALLIANCE / TYRES / PRODUCT SPECIFICATION

# 600/65-34 Alliance 346 FORESTAR 157A8 / 164A2 14 PR

Forestar 346 Forestry Flotation is a bias belted tire with steel reinforcement for high puncture resistance. The tire has a special tread compound and has very thick sidewalls and under tread. The reinforced bead of the tire provides exceptional performance. Its lower lug angle provides excellent grip and exhibits self cleaning characteristics due to its wide inter-lug space which is vital in logging applications. The close spacing of the lugs in the centre of the tire reduces rolling resistance on hard surfaces. The 346 is designed to handle various terrains without chains/bogie trucks.



## Technical specification

|                            |                |
|----------------------------|----------------|
| Brand                      | Alliance       |
| Range                      | 346 FORESTAR   |
| Size                       | 600/65-34      |
| Section width (mm)         | 600            |
| Overall diameter (mm)      | 1640           |
| Loaded static radius (mm)  | 762            |
| Rolling circumference (mm) | 4927           |
| Listed rims                | DW20A          |
| Rating                     | 14 157A8 164A2 |
| Ply rating                 | 14             |
| Load index                 | 157 / 164      |
| Speed rating               | A8 / A2        |
| Service description        | 157A8 / 164A2  |

## Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.