



## ALLIANCE / TYRES / PRODUCT SPECIFICATION

## 18.4-38 Alliance 356 155A8 / 162A2 14 PR

The 356 is a tire for high power tractors on heavy duty jobs in forestry and heavier operation in agriculture. The tire is designed for high traction abilities, low slip and low fuel consumption. The main construction characteristics of the tire are: strong nylon casing, high under tread gauge, strong and thick sidewalls, special tread compound and protective mud guard. All these characteristics promise long tire life under heavy working conditions in the forests, as well as, smooth and long lasting work in agriculture. In addition, high non-skid depth promises high traction forces on cohesive and wet soil.



### Technical specification

|                            |                          |
|----------------------------|--------------------------|
| Brand                      | Alliance                 |
| Range                      | 356                      |
| Size                       | 18.4-38                  |
| Section width (mm)         | 467                      |
| Overall diameter (mm)      | 1750                     |
| Loaded static radius (mm)  | 806                      |
| Rolling circumference (mm) | 5284                     |
| Listed rims                | W16 W16L W16A W15L DW15L |
| Rating                     | 14 155A8 162A2           |
| Ply rating                 | 14                       |
| Load index                 | 155 / 162                |
| Speed rating               | A8 / A2                  |
| Service description        | 155A8 / 162A2            |

### Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.