



## ALLIANCE / TYRES / PRODUCT SPECIFICATION

## 600/65R28 Alliance 360 154A8 / 161A2

Alliance 360 is an extra wide tire available in radial for use in agricultural tractors and combine harvesters for farming. It is characterised by increased load capacity for the same inflation pressure. This means that the low inflation pressure combined with large footprint helps reduce soil compaction. Low angled lugs of the tire at the shoulder area improve traction, while higher angles around the tire centre line improve ride comfort. This leads to increased tire traction efficiency by an effective traction/slip characteristic. Also the strong radial construction with reinforced beads and sidewalls provide long tire life.



### Technical specification

|                            |               |
|----------------------------|---------------|
| Brand                      | Alliance      |
| Range                      | 360           |
| Size                       | 600/65R28     |
| Section width (mm)         | 600           |
| Overall diameter (mm)      | 1486          |
| Loaded static radius (mm)  | 678           |
| Rolling circumference (mm) | 4481          |
| Listed rims                | W18L          |
| Rating                     | 154A8 161A2   |
| Load index                 | 154 / 161     |
| Speed rating               | A8 / A2       |
| Service description        | 154A8 / 161A2 |

### Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.