



## ALLIANCE / TYRES / PRODUCT SPECIFICATION

## 600/50R22.5 Alliance 882 162D / 159E

Alliance 882 Implement tire combines the best characteristics of flotation tires and radial construction to provide superior performances on road and in field applications. One of its salient features is a strong fabric carcass reinforced by rigid steel belts. Its directional block configuration ensures best possible self cleaning ability and assists in keeping on/ off the road travel direction. Due to its huge internal volume the tire is characterized by low inflation pressure that promises low soil compaction for very high load capacity. This tire's stiffness is increased in both radial and lateral directions by additional ply added to the basic carcass.



### Technical specification

|                            |             |
|----------------------------|-------------|
| Brand                      | Alliance    |
| Range                      | 882         |
| Size                       | 600/50R22.5 |
| Section width (mm)         | 611         |
| Overall diameter (mm)      | 1172        |
| Loaded static radius (mm)  | 528         |
| Rolling circumference (mm) | 3565        |
| Listed rims                | AG20.00     |
| Rating                     | 162D (159E) |
| Load index                 | 162 / 159   |
| Speed rating               | D / E       |
| Service description        | 162D / 159E |

### Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.