



ALLIANCE / TYRES / PRODUCT SPECIFICATION

480/65-28 Alliance AF 669 142A8 / 139B

Alliance AF669 is an extra wide tire available in radial for use in Forestry tractors. It is characterized by increased load capacity for the same inflation pressure. This means that the low inflation pressure combined with a large footprint helps reduce soil compaction. Low- angled lugs of the tire at the shoulder area improve traction, while higher angles around the tire center line improve ride comfort. This leads to increased tire traction efficiency by an effective traction/slip characteristic. Also, the strong radial construction with reinforced beads and sidewalls provides a long tire life. Wide inter-lug spacing ensures good self-cleaning. The reinforced side walls with additional rubber and textile layer provide excellent stability during forestry operations. The tire is built with special forestry compounds and a tough sidewall for effective forestry use. Steel belt layers provide protection against punctures under severe working conditions in the forest.



Technical specification

Brand	Alliance
Range	AF 669
Size	480/65-28
Section width (mm)	470
Overall diameter (mm)	1350
Loaded static radius (mm)	628
Rolling circumference (mm)	4034
Listed rims	W15L
Rating	142A8 139B
Load index	142 / 139
Speed rating	A8 / B
Service description	142A8 / 139B

Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.