



ALLIANCE / TYRES / PRODUCT SPECIFICATION

VF480/80R50 Alliance AGRIFLEX+ 354 171D / 179D

The advanced 354 AGRIFLEX+ Very High Flexion (VF) is designed to carry same load as standard radial tractor tire but at lower pressure or carry upto 40% more at the same pressure. Together with all the advantages of Alliance's standard R-1W radial tractor drive tires, these tires allow lower inflation pressure for the same load capacity related to regular Row Crop tires. Stronger lugs, outstanding traction, excellent self-cleaning characteristics and enhanced lug shape ensure exceptional durability, comfort and a significant reduction of noise while driving on the road. Agriflex+ 354 gives a large tire footprint area for high traction, reduces fuel costs and increases overall productivity and provides high puncture protection and uniform ground pressure distribution due to its steel belts.



Technical specification

Brand	Alliance
Range	AGRIFLEX+ 354
Size	VF480/80R50
Section width (mm)	494
Overall diameter (mm)	2054
Loaded static radius (mm)	942
Rolling circumference (mm)	6127
Listed rims	W16
Rating	171D 179D
Load index	171 / 179
Speed rating	D
Service description	171D / 179D

Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.