



## ALLIANCE / TYRES / PRODUCT SPECIFICATION

# 460/85R30 (18.4R30) Alliance FARMPRO RADIAL 85 145A8 / 145B

FarmPRO '85 Series of agricultural radial tires have multi angle lug design with steep angles at the center that enables smooth ride along with self cleaning characteristics. The shallow angle at shoulder provides superior traction. These tires are characterized by reinforced construction in the bead area and have enhanced bead to bead distance to facilitate perfect fit on the rim. The regular cavity in the tread design ensures a straighter sidewall.



## Technical specification

|                            |                       |
|----------------------------|-----------------------|
| Brand                      | Alliance              |
| Range                      | FARMPRO RADIAL 85     |
| Size                       | 460/85R30 (18.4R30)   |
| Section width (mm)         | 478                   |
| Overall diameter (mm)      | 1524                  |
| Loaded static radius (mm)  | 680.4                 |
| Rolling circumference (mm) | 4509                  |
| Listed rims                | DW15L W15L W16L DW16L |
| Rating                     | 145A8 145B            |
| Load index                 | 145                   |
| Speed rating               | A8 / B                |
| Service description        | 145A8 / 145B          |

## Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.