



## ALLIANCE / TYRES / PRODUCT SPECIFICATION

# 400/80R24IND (14.9R24IND) Alliance MULTIUSE 550 149A8 / 144D

550 MULTIUSE pattern is used in agricultural applications because of its versatile tread design. Specific block tread design enables high performances on snow-covered terrains, as well as on sandy terrains. Basic directional lug design, divided by separated blocks, provides a good grip on soft surfaces. In addition, high number of blocks and rubber to void tread ratio, enables long tread wear life and low rolling resistances during transport operation on hard surfaces. Uniform ground pressure distribution and tread wear are provided by steel belted carcass structure. In addition, steel belts provide the most efficient puncture protection.



## Technical specification

|                            |                           |
|----------------------------|---------------------------|
| Brand                      | Alliance                  |
| Range                      | MULTIUSE 550              |
| Size                       | 400/80R24IND (14.9R24IND) |
| Section width (mm)         | 404                       |
| Overall diameter (mm)      | 1249                      |
| Loaded static radius (mm)  | 566                       |
| Rolling circumference (mm) | 3730                      |
| Listed rims                | W13                       |
| Rating                     | 149A8 144D                |
| Load index                 | 149 / 144                 |
| Speed rating               | A8 / D                    |
| Service description        | 149A8 / 144D              |

## Specification notes

Multiple service descriptions are listed for this size. Tell us your application, load and speed so the required specification can be confirmed.