



## PRONAR / WHEELS / PRODUCT SPECIFICATION

## W10x34 Pronar Ring and waffle wheels

Adjustable tractor wheels with continuous ring constructions. The catalogue lists crown, flat and pressed ring options, with disc and offset choices for each size.



### Technical specification

|                                      |                        |
|--------------------------------------|------------------------|
| Brand                                | Pronar                 |
| Range                                | Ring and waffle wheels |
| Size                                 | W10x34                 |
| Wheel diameter (inches)              | 34"                    |
| Rim profile                          | W10                    |
| Tyre sizes                           | 320/85R34              |
| Type of ring                         | FDW/FFW                |
| Maximum ring offset (mm), crown/flat | +70.5/-70.5            |
| Ring thickness (mm)                  | 8/10/12                |
| Maximum ring offset (mm), pressed    | +100/-120              |
| Pressed ring thickness               | 8                      |
| Disc profiles                        | SF; ODF; OFR;          |
| Disc offset (mm)                     | 75; 100; 107;          |
| Disc thickness (mm)                  | 8; 10; 12              |

### Specification notes

The given load capacities refer to the optimal strength combinations and are not available for all connections and offsets.

FFW: Fully Formed Welded; FDW: Flat Double Welded; FCDW: Flat Crown Double Welded. CCD footnote 1: Crown Cut disc - disc obtained after cutting a four or eight-arm shaped crown.