



## PRONAR / WHEELS / PRODUCT SPECIFICATION

## W12x50 Pronar Ring and waffle wheels

Adjustable tractor wheels with continuous ring constructions. The catalogue lists crown, flat and pressed ring options, with disc and offset choices for each size.



### Technical specification

|                                      |                          |
|--------------------------------------|--------------------------|
| Brand                                | Pronar                   |
| Range                                | Ring and waffle wheels   |
| Size                                 | W12x50                   |
| Wheel diameter (inches)              | 50"                      |
| Rim profile                          | W12                      |
| Tyre sizes                           | 380/105R50; 380/90R50    |
| Type of ring                         | FDW; FCDW                |
| Maximum ring offset (mm), crown/flat | +96/-96                  |
| Ring thickness (mm)                  | 12; 14                   |
| Maximum ring offset (mm), pressed    | -                        |
| Pressed ring thickness               | -                        |
| Disc profiles                        | SF; OF; OFR; OFD; CCD[1] |
| Disc offset (mm)                     | 65; 100;                 |
| Disc thickness (mm)                  | 12; 14;                  |

### Specification notes

The given load capacities refer to the optimal strength combinations and are not available for all connections and offsets.

FFW: Fully Formed Welded; FDW: Flat Double Welded; FCDW: Flat Crown Double Welded. CCD footnote 1: Crown Cut disc - disc obtained after cutting a four or eight-arm shaped crown.