



## PRONAR / WHEELS / PRODUCT SPECIFICATION

## DW15Lx38 Pronar Tractor fixed wheels

Fixed disc wheels for agricultural tractors, with pressed disc profiles and catalogue sizes from 12 to 42 inches. Load capacity depends on the material, offset and connection specified for the wheel.



### Technical specification

|                               |                             |
|-------------------------------|-----------------------------|
| Brand                         | <b>Pronar</b>               |
| Range                         | <b>Tractor fixed wheels</b> |
| Size                          | <b>DW15Lx38</b>             |
| Wheel diameter (inches)       | <b>38"</b>                  |
| Rim profile                   | <b>DW15L</b>                |
| Tyre sizes                    | <b>420/85R38; 480/70R38</b> |
| Load capacity (kg) at 40 km/h | <b>4600</b>                 |
| Maximum offset ranges (mm)    | <b>+149/-163</b>            |
| Disc profile                  | <b>DF; DFC; F; FFC; TFC</b> |

### Specification notes

The given load capacities refer to the optimal strength combinations and are not available for all connections and offsets.

Presented load capacity available only in the heaviest material option, with maximum offset and standard PCD.

Negative offset available only in the event of assembling the wheel with valve guard on the machine's side.

Actual shape of the disc may slightly differ from the presented model.